

# RPL-HT600 Synthetic, High Temperature Grease

# **SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION**

Product Identification: RPL-HT600

**Synthetic, High Temperature Grease** 

Supplier Identification: Davley Darmex Lubricants

7370 Bramalea Rd., Unit 38, Mississauga, Ontario, Canada L5S 1N6 Phone: (905) 795-1150 Fax: (905) 795-1151 Toll Free: 1-800-361-9458

Email: sales@davley-darmex.com

Hours: Monday to Friday, 8:00AM - 5:00PM EDT

MSDS Print Date: March 28, 2017

### **SECTION 2 – COMPONENT DATA**

This product is a semi-solid that is insoluble in water. Direct eye contact may cause minor, short-term irritation. Short-term skin exposure is not expected to be irritating. Inhalation of mist or vapor may be irritating. Polytetrafluoroethylene (PTFE), when thermally decomposed (over 290C), may cause polymer fume fever.

HMIS Rating: Health: 1 Flammability: 1 Reactivity: 0 PPE: X

Components listed in this section may contribute to the potential hazards associated with exposure to the concentrate. The product may contain additional non-hazardous or trade secret components.

This product contains no known hazardous ingredients. A threshold limit value of 5 mg/m3 is suggested for oil mist in air.

None of the components of this product at concentrations greater than or equal to 0.1% are listed as a carcinogen or potential carcinogen by NTP, IARC, OSHA

### **SECTION 3 – HAZARDOUS IDENTIFICATION**

#### POTENTIAL HEALTH EFFECTS and SYMPTOMS from SHORT / ACUTE EXPOSURE:

#### **EYE EXPOSURE**

This product is not expected to cause eye irritation under normal conditions of use. Symptoms of slight eye irritation may result when direct contact occurs, or when exposed to high mist levels in poorly ventilated areas.

Product: RPL-HT600 Page 1 of 7



#### SKIN EXPOSURE

Short-term skin exposure is not expected to cause skin irritation. Prolonged or repeated direct exposure to the skin may result in symptoms of irritation and redness. In severe cases, prolonged or repeated contact may result in dermatitis accompanied by symptoms of irritation, itching, dryness, cracking and / or inflammation.

#### INHALATION

This product has low volatility and so is not expected to cause respiratory tract irritation during normal conditions of use. At elevated temperatures, vapor or mists may be produced which may cause irritation to the respiratory tract.

#### **INGESTION**

Do not induce vomiting. Small amounts aspirated into lungs during ingestion or vomiting may cause mild to severe pulmonary injury. Ingestion may cause slight stomach irritation and discomfort.

#### POTENTIAL CHRONIC HEALTH EFFECTS

Prolonged and/or repeated exposure to eyes, skin or respiratory tract may cause irritation.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

No further data known

#### **CARCINOGENICITY**

This product is not listed as a known or suspected carcinogen by IARC, OSHA, or the NTP.

# **SECTION 4 – FIRST AID MEASURES**

#### **EYE CONTACT**

Upon direct eye contact, hold eyelids open flush with a steady, gentle stream of water for at least 15 minutes. If irritation is due to exposure to mist or vapors, remove the individual to fresh air. If irritation persists, flush the eyes with clean water until the irritation subsides. If symptoms persist, contact physician.

#### **SKIN CONTACT**

Remove product from the skin by washing with mild soap and water. Contaminated clothing should be removed to prevent prolonged exposure. If symptoms of exposure persist, contact physician.

#### **INHALATION**

Inhalation is not an expected route of exposure. If respiratory irritation or distress occurs remove the employee to fresh air. Contact a physician or other medical professional if irritation or distress persists.

#### INGESTION

If small amounts are ingested, first aid measures are not likely to be necessary. If larger amounts are ingested or if symptoms of ingestion occur, dilute stomach contents with two glasses of water or milk. (NOTE: DO NOT give anything by mouth to an unconscious person). Do not induce vomiting without medical supervision. If vomiting occurs spontaneously keep airway clear. If symptoms of ingestion persist, seek medical attention.

#### **NOTE TO PHYSICIAN**

No further data known

Product: RPL-HT600 Page 2 of 7



# <u>SECTION 5 – FIRE FIGHTING MEASURES AND DATA</u>

# FIRE AND EXPLOSION PROPERTIES

Flash Point: 500.0 °F COC Flammability Limits: LEL N/A UEL N/A

#### **EXTINGUISHING MEDIA**

In accordance with NFPA guidance, dry chemical, foam, or CO2 fire extinguishers are all acceptable. Note that while water fog extinguishers are also acceptable, do NOT apply a direct stream of water onto burning product because it may cause spreading and increase fire intensity.

#### **UNUSUAL FIRE & EXPLOSION HAZARDS**

No further data known.

#### FIRE-FIGHTING PROCEDURES AND EQUIPMENT

Emergency responders in the danger areas should wear bunker gear and self-contained breathing apparatus for fires beyond the incipient stage. See section 8 of the MSDS for other PPE to be worn as conditions warrant.

# **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

#### **CLEAN-UP MEASURES:**

**Important:** As with any spill or leak, ensure before responding that you are familiar with the potential hazards and recommendations of the MSDS. Appropriate personal protective equipment must be worn. See Section 8 of this MSDS for PPE recommendations.

If possible, safely contain the spill with dikes or other spill response equipment appropriate for petroleum or organic material releases. Take measures to prevent spreading of product. Note that while product will ignite, it will not readily burn. However, as a precaution eliminate ignition sources. Prevent from entering sewers or waterways. Large volumes may be transferred to an appropriate container for proper disposal. Small volumes or residues may be soaked up with absorbents. Spill response materials should be collected for proper disposal.

## **SECTION 7 – HANDLING AND STORAGE**

#### **HANDLING**

As with any industrial chemical, handle the product in a manner that minimizes exposure to practicable levels. Prior to handling, consult Section 8 of this MSDS to evaluate personal protective equipment needs. Open containers slowly to relieve any pressure. Follow all other standard industrial hygiene practices.

Empty containers may contain product residue. All safety precautions taken when handling this product should also be taken when handling empty drums and containers. Keep containers closed when not in use. Product residue in empty containers is combustible but will not readily burn. NOTE however, that excessive heating or cutting of empty containers may create an ignition source sufficient to start a fire and in extreme cases, cause an explosion.

#### **STORAGE**

Protect product quality by storing indoors and away from extreme temperatures. Close all containers when not in use.

Product: RPL-HT600 Page 3 of 7



#### **SPECIAL COMMENTS**

No further data known.

# **SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION**

#### PERSONAL PROTECTIVE EQUIPMENT

Selection of personal protective equipment should be based upon the anticipated exposure and made in accordance with OSHA's Personal Protective Equipment Standard found in 29 CFR 1910 Subpart I. The following information may be used to assist in PPE selection.

#### **EYE PROTECTION**

Wear eye protection appropriate to prevent eye exposure. Where splashing is not likely, chemical safety glasses with side shields are recommended. Where splashing may occur, chemical goggles or full-face shield is recommended.

#### SKIN PROTECTION

Gloves are not normally needed during normal conditions of use. If health effects are experienced, oil or chemical resistant gloves such as butyl or nitrile are recommended. Where splashing or soaking is likely, wear oil or chemical resistant clothing to prevent exposure.

#### RESPIRATORY PROTECTION

A respirator may be worn to reduce exposure to vapors, dust, or mist. Select a NIOSH / MSHA approved respirator appropriate for the type and physical character of the airborne material. A self-contained breathing apparatus is recommended in all situations where airborne contaminant concentration has not been confirmed to be below safe levels. Respirator use should comply with the OSHA Respirator Protection Standard found in 29 CFR 1910.134.

#### **ENGINEERING CONTROLS**

Normal general ventilation is expected to be adequate. It is recommended that ventilation be designed in all instances to maintain airborne concentrations at lower practicable levels. Ventilation should at a minimum, prevent airborne concentrations from exceeding any exposure limits listed in Section 2 of this MSDS.

The user may wish to refer to 29 CFR 1910.1000 (d) (2) and ACGIH "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices" (Appendix C) for the determination of exposure limits of mixtures. An industrial hygienist or similar professional may be consulted to confirm that the calculated exposure limits apply.

### **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Physical Appearance: Off-White

Odor: Mild Petroleum
Physical State: Semi-solid Grease

Specific Gravity: .980 Water Solubility: Insoluble

Evaporation Rate (Butyl acetate=1): < 1

Product: RPL-HT600 Page 4 of 7

# **SECTION 10 – STABILITY AND REACTIVITY**

#### **INCOMPATIBILITIES**

This product is incompatible with strong oxidizing agents.

# **DECOMPOSITION PRODUCTS MAY INCLUDE**

Thermal decomposition products are dependent on combustion conditions. A complex mixture of airborne solid, liquid, particulates and gasses may evolve when the material burns. Combustion byproducts may include:

- Oxides of phosphorous
- Oxides of nitrogen
- Traces of hydrogen sulfide
- Oxides of carbon
- Incompletely burned hydrocarbons as fumes and smoke.

#### **CONDITIONS TO AVOID**

Avoid contact with incompatible materials and exposure to extreme temperatures.

#### **POLYMERIZATION**

This product is not expected to polymerize.

#### **STABILITY**

This product is stable.

# SECTION 11 – TOXICOLOGICAL INFORMATION

#### **EYE EFFECTS**

No further toxicological data known.

### **SKIN EFFECTS**

No further toxicological data known.

#### **ORAL EFFECTS**

No further toxicological data known.

#### **INHALATION EFFECTS**

No further toxicological data known.

#### **OTHER**

No further toxicological data known.

### **SECTION 12 – ECOLOGICAL INFORMATION**

#### **ECOTOXICOLOGICAL INFORMATION**

This product has not been evaluated for ecotoxicity. As with any industrial chemical, exposure to the environment should be prevented and minimized wherever possible.

Product: RPL-HT600 Page 5 of 7



#### **ENVIRONMENTAL FATE**

The degree of biodegradability and persistence of this product has not been determined.

# **SECTION 13 – DISPOSAL CONSIDERATION**

#### **WASTE DISPOSAL**

Ensure that collection, transport, treatment, and disposal of waste product, containers and rinsate comply with all applicable laws and regulations. Note that use, mixture, processing, or contamination of the product may cause the material to be classified as a hazardous waste. It is the responsibility of the product user or owner to determine at the time of disposal, whether the product is regulated as a hazardous waste.

# **SECTION 14 – TRANSPORT INFORMATION**

# **DOT HAZARDOUS MATERIAL INFORMATION**

Not otherwise DOT regulated.

# **SECTION 15 – REGULATORY INFORMATION**

#### **FEDERAL REGULATIONS**

SARA 313: This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and reauthorization Act of 1986 and 40 CFR Part 372.

#### **CLEAN WATER ACT / OIL POLLUTION ACT**

This product contains mineral oil and is subject to regulations by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to surface waters must be reported to the National Response Center at 1-800-424-8802.

#### **CERCLA REPORTABLE QUANTITY:**

(NONE FOUND IN THIS PRODUCT)

Any components listed below have been assigned a reportable quantity (RQ) by the Federal EPA. Releases of the product into the environment that exceed the RQ for a particular component must be reported to the National Response Center at 1-800-424-8802.

COMPONENT(NONE FOUND IN THIS PRODUCT)	RQ
TOXIC SUBSTANCES CONTROL ACT	
The components of this product are listed on the TSCA Inventory.	
<b>OZONE DEPLETING SUBSTANCES</b> The product contains no ozone depleting substances as defined by the Clean Air Act.	
HAZARDOUS AIR POLLUTANTS  The Federal EPA defines any components listed below as hazardous air pollutants.	
COMPONENT	RQ

Product: RPL-HT600 Page 6 of 7



#### **STATE REGULATIONS**

This product contains mineral oil, and as used, may be regulated by state used oil regulations. Check with the appropriate state agency to determine whether such a regulation exists.

No further data known.

# <u>SECTION 16 – OTHER INFORMATION</u>

Date of Issue: 1/15/2015

#### NOTICE OF DISCLAIMER

Please note that all information provided in these MSDS sheets have been carefully edited by Davley Darmex Lubricants and are considered to be accurate at the time of issue. However, no responsibility for possible errors or omissions can be assumed and the company reserves the right to change without notice. Davley Darmex assumes no legal responsibility or warranty either expressly or by implication based on this data. Please also note that the chemical identity of some or all of the ingredients may be withheld as confidential business information as permitted by 29 CFR 1910.1200 and other relevant legislation. Duplication in whole or in part of this information without written consent is prohibited. © Davley Darmex Lubricants.

Product: RPL-HT600 Page 7 of 7